

Technical Data Sheet

Technical Information		
Standby Power (ESP)	kVA	250
	kW	200
Prime Power (PRP)	kVA	225
	kW	180
Power Factor	cos ϕ	0,8
Frequency	Hz	50
Voltage	V	230/400

Standby Power (ESP)

Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power (PRP)

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.



Weight and Dimensions

Length	mm	4000
Width	mm	1300
Height	mm	1900
Weight	kg	2500
Fuel tank capacity	Liters	350
Model	Soundproof canopy	

Engine		Doosan
Model	-	DP086LA
No. of cylinders	-	6 in line
Engine Capacity	c.c.	8071
Bore	mm	111
Stroke	mm	139
Compression ratio	-	16,7:1
Cooling system	-	Water
Governor type	-	Electronic
Speed	rpm	1500
Engine Gross Power	kWm	219
Lubrication Oil Capacity	liters	15,5
Coolant Capacity	liters	44
Water jacket heater	-	Yes
Battery charger	-	Yes
Fuel Consumption	100%	54,4 L/h
	75%	39,8 L/h
	50%	26,0 L/h

Alternator		WEG
Model	-	250SI20AI
Power (Standby)	kVA	277
Excitation System	-	AVR, Brushless
Degree of Protection	-	IP 23

Control panel		Deep Sea - UK
Instruments	Alarms	
Voltmeter	Start-up failure	
Ammeter	Battery charge failure	
Frequency meter	Low oil pressure	
Hour meter	High engine water temperature	
Events history	Low Fuel Level	
Display LCD+LED	Emergency Stop	
Communication port	Over speed	

- Product certified according ISO 9001, ISO 14001 and CE standards.
- The information and images contained in this document are for general purposes and are subject to change without prior notice.



MARRO ELECTRIC SYSTEMS

Bucharest, Romania

office@marro.ro

www.marro.ro